Distributed by:

JAMECO® ELECTRONICS

www.Jameco.com ✦ 1-800-831-4242

The content and copyrights of the attached material are the property of its owner.

2N4918 thru 2N4920*

*ON Semiconductor Preferred Device

Medium-Power Plastic PNP Silicon Transistors

. . . designed for driver circuits, switching, and amplifier applications. These high–performance plastic devices feature:

- Low Saturation Voltage — $V_{CE(sat)}$ = 0.6 Vdc (Max) @ I_C = 1.0 Amp
- Excellent Power Dissipation Due to Thermopad Construction — P_D = 30 W @ T_C = 25°C
- Excellent Safe Operating Area
- Gain Specified to I_C = 1.0 Amp
- Complement to NPN 2N4921, 2N4922, 2N4923

3 AMPERE GENERAL–PURPOSE POWER TRANSISTORS 40–80 VOLTS 30 WATTS



CASE 77–09 TO–225AA TYPE

***MAXIMUM RATINGS**

Ratings	Symbol	2N4918	2N4919	2N4920	Unit
Collector–Emitter Voltage	V_{CEO}	40	60	80	Vdc
Collector–Base Voltage	V_{CB}	40	60	80	Vdc
Emitter–Base Voltage	V_{EB}	5.0			Vdc
Collector Current — Continuous (1)	I_C*	1.0 3.0			Adc
Base Current	I_B	1.0			Adc
Total Power Dissipation @ T_C = 25°C Derate above 25°C	P_D	30 0.24			Watts W/°C
Operating & Storage Junction Temperature Range	T_J, T_{stg}	–65 to +150			°C

THERMAL CHARACTERISTICS (2)

Characteristic	Symbol	Max	Unit
Thermal Resistance, Junction to Case	θ_{JC}	4.16	°C/W

*Indicates JEDEC Registered Data for 2N4918 Series.

(1) The 1.0 Amp maximum I_C value is based upon JEDEC current gain requirements. The 3.0 Amp maximum value is based upon actual current–handling capability of the device (See Figure 5).

(2) Recommend use of thermal compound for lowest thermal resistance.

Preferred devices are ON Semiconductor recommended choices for future use and best overall value.

© Semiconductor Components Industries, LLC, 2002



Figure 1. Power Derating

ELECTRICAL CHARACTERISTICS (T_C = 25°C unless otherwise noted)

Characteristic		Symbol	Min	Max	Unit
OFF CHARACTERISTICS					
Collector–Emitter Sustaining Voltage (1) (I_C = 0.1 Adc, I_B = 0)	2N4918 2N4919 2N4920	$V_{CEO(sus)}$	 40 60 80	 — — —	Vdc
Collector Cutoff Current (V_{CE} = 20 Vdc, I_B = 0) (V_{CE} = 30 Vdc, I_B = 0) (V_{CE} = 40 Vdc, I_B = 0)	 2N4918 2N4919 2N4920	I_{CEO}	 — — —	 0.5 0.5 0.5	mAdc
Collector Cutoff Current (V_{CE} = Rated V_{CEO}, $V_{BE(off)}$ = 1.5 Vdc) (V_{CE} = Rated V_{CEO}, $V_{BE(off)}$ = 1.5 Vdc, T_C = 125°C		I_{CEX}	 — —	 0.1 0.5	mAdc
Collector Cutoff Current (V_{CB} = Rated V_{CB}, I_E = 0)		I_{CBO}	—	0.1	mAdc
Emitter Cutoff Current (V_{BE} = 5.0 Vdc, I_C = 0)		I_{EBO}	—	1.0	mAdc
ON CHARACTERISTICS					
DC Current Gain (1) (I_C = 50 mAdc, V_{CE} = 1.0 Vdc) (I_C = 500 mAdc, V_{CE} = 1.0 Vdc) (I_C = 1.0 Adc, V_{CE} = 1.0 Vdc)		h_{FE}	 40 30 10	 — 150 —	—
Collector–Emitter Saturation Voltage (1) (I_C = 1.0 Adc, I_B = 0.1 Adc)		$V_{CE(sat)}$	—	0.6	Vdc
Base–Emitter Saturation Voltage (1) (I_C = 1.0 Adc, I_B = 0.1 Adc)		$V_{BE(sat)}$	—	1.3	Vdc
Base–Emitter On Voltage (1) (I_C = 1.0 Adc, V_{CE} = 1.0 Vdc)		$V_{BE(on)}$	—	1.3	Vdc
SMALL–SIGNAL CHARACTERISTICS					
Current–Gain — Bandwidth Product (I_C = 250 mAdc, V_{CE} = 10 Vdc, f = 1.0 MHz)		f_T	3.0	—	MHz
Output Capacitance (V_{CB} = 10 Vdc, I_E = 0, f = 100 kHz)		C_{ob}	—	100	pF
Small–Signal Current Gain (I_C = 250 mAdc, V_{CE} = 10 Vdc, f = 1.0 kHz)		h_{fe}	25	—	—

*Indicates JEDEC Registered Data.
(1) Pulse Test: PW ≈ 300 μs, Duty Cycle ≈ 2.0%



Figure 2. Switching Time Equivalent Test Circuit



Figure 3. Turn–On Time



Figure 4. Thermal Response



Figure 5. Active−Region Safe Operating Area

There are two limitations on the power handling ability of a transistor: average junction temperature and second breakdown. Safe operating area curves indicate $I_C - V_{CE}$ operation i.e., the transistor must not be subjected to greater dissipation than the curves indicate.

The data of Figure 5 is based on $T_{J(pk)} = 150°C$; T_C is variable depending on conditions. Second breakdown pulse limits are valid for duty cycles to 10% provided $T_{J(pk)} \leq 150°C$. At high case temperatures, thermal limitations will reduce the power that can be handled to values less than the limitations imposed by second breakdown.



Figure 6. Storage Time



Figure 7. Fall Time

TYPICAL DC CHARACTERISTICS



Figure 8. Current Gain



Figure 9. Collector Saturation Region



Figure 10. Effects of Base−Emitter Resistance



Figure 11. "On" Voltage



Figure 12. Collector Cut−Off Region


*APPLIES FOR I_C/I_B < $\frac{h_{FE} @ V_{CE} = 1.0 V}{2}$
T_J = 100°C to 150°C
*θ_{VC} FOR $V_{CE(sat)}$
T_J = −55°C to +100°C
θ_{VB} FOR V_{BE}
TEMPERATURE COEFFICIENTS (mV/°C)
I_C, COLLECTOR CURRENT (mA)

Figure 13. Temperature Coefficients

PACKAGE DIMENSIONS

TO−225AA
CASE 77−09
ISSUE W



NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.

	INCHES		MILLIMETERS	
DIM	MIN	MAX	MIN	MAX
A	0.425	0.435	10.80	11.04
B	0.295	0.305	7.50	7.74
C	0.095	0.105	2.42	2.66
D	0.020	0.026	0.51	0.66
F	0.115	0.130	2.93	3.30
G	0.094 BSC		2.39 BSC	
H	0.050	0.095	1.27	2.41
J	0.015	0.025	0.39	0.63
K	0.575	0.655	14.61	16.63
M	5° TYP		5° TYP	
Q	0.148	0.158	3.76	4.01
R	0.045	0.065	1.15	1.65
S	0.025	0.035	0.64	0.88
U	0.145	0.155	3.69	3.93
V	0.040	---	1.02	---

STYLE 1:
PIN 1. EMITTER
2. COLLECTOR
3. BASE

Notes

ON Semiconductor and are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer.

PUBLICATION ORDERING INFORMATION

Literature Fulfillment:
Literature Distribution Center for ON Semiconductor
P.O. Box 5163, Denver, Colorado 80217 USA
Phone: 303–675–2175 or 800–344–3860 Toll Free USA/Canada
Fax: 303–675–2176 or 800–344–3867 Toll Free USA/Canada
Email: ONlit@hibbertco.com

N. American Technical Support: 800–282–9855 Toll Free USA/Canada

JAPAN: ON Semiconductor, Japan Customer Focus Center
4–32–1 Nishi–Gotanda, Shinagawa–ku, Tokyo, Japan 141–0031
Phone: 81–3–5740–2700
Email: r14525@onsemi.com

ON Semiconductor Website: http://onsemi.com

For additional information, please contact your local
Sales Representative.

AN4918/D